



✓ HIGHER RESOLUTION
✓ LOWER DOSE



Image Capture Review

IMAGE

3600 | HD RESOLUTION CR

VertX is a scalable design that allows for the highest efficiency Crystal IP phosphor screens, 16 Bit available gray scale, and upgradable features that provide users with stunning 10 lp/mm maximum resolution.

CAPTURE

XC | ACQUISITION

XC touchscreen acquisition with ICE-3 Enhancement Processing provides all-new features including, "Image Display State" to ensure balanced presentation of both soft tissue, overlapping bone structures, and automatic analysis of image characteristics to optimize processing.

REVIEW

CLARITY PACS

Our fully web-enabled and integrated PACS solutions help transition your practice into a safe, secure, and filmless environment.

Clarity PACS™ supports all your current and future imaging needs.

icrco.com



16 | Bit Resolution

75 | Plates Per/Hr

50 | Lbs

Highly Portable | **One Moving** Part | **Military** Choice

VertX[™], the Choice of the United States Military was designed with tough in mind. This portable CR offers a flexible digital imaging solution for all medical imaging environments that withstood several vigorous military environmental testing procedures.

Physicians can achieve amazing workflow at a much lower cost with its integrated pairing with the robust and feature-rich image processing **XC™** software. **XC** provides superior quality images every time with an option to further manipulate the images.







Although computed radiography technology has been widely accepted, other major manufacturers follow the same pattern of removing the costly phosphor plates and running them through rollers in their CR readers. iCRco has re-invented how CR technology works with **True Flat Scan Path™**. This technology ensures the phosphor plate never leaves the cassette to avoid any plate handling, damage or wear during the scan process.

VERTX™ FEATURES

- Choice of the U.S. Military
- Passed vigorous military testing
- Easily mounted on a GE AMX-4*
- Mobile or stationary
- Superior image processing software
- Small footprint and simple to use.

*GE AMX-4 is a trademark of GE

SEIZE THE **FUTURE** OF MEDICAL IMAGING

WITH iCRco

VertX[™] Specifications*

Micron Spot Size	Pixels Per mm	Dots Per Inch (DPI)	Line Pairs Per mm
155	5	163	3.1
100	10	254	5

Grayscale resolution	16 bits/pixel source file, 65536 shades of gray		
Image access time	35 seconds		
Configuration	Portable or smallest stationary CR		
Weight	50 lbs		
Dimensions	W21" x D8.15" x H35" (W112 x D31 x H59 cm)		
Power source	100-240V AC/ 2.5A max; 47-63Hz (universal power supply)		
iSupply	24V portable DC power supply available, 270 scans on single charge		
Heat generation	Standby 230W, maximum 1610W		
Operating conditions	Temperature; 0-40°C/32-105°F, temperature change: 0.5°C/min, humidity: 15%-95% RH, magnetic fields: max 1260 μ T (in conformance with EN 61000-4-8: Level 3), 10 A/m		

^{*} Specifications are subject to change without notice. Processing and display time dependent on processor speed, RAM disk access time, and video card.



Components are made from 98% recyclable parts • iCRco is an ISO 13485 certified company • U.S. and international patents granted • Additional patents pending • FDA

© 2014 iCRco. All rights reserved. "VertX" and "XC" are registered trademarks of iCRco. BR093014AUS

XC[™] Acquisition Software Features

XC - Intuitive touchscreen acquisition

ICE-3 Processing - Automated image characteristics analysis for maximum image enhancement

Image Display State: Automated enhancement of image display at the point of acquisition

Smart search, sort, and filter options

Integration with front office management systems like RIS and EMR

Full set of annotation and measurement tools

User-preferred settings and privileges

Outer Dimensions





